



MIDAS WINDOW FILM™

THANKS FOR TRUSTING US!

	Visible Light Transmittance	Total Solar Transmittance	Total Solar Reflectance	Total Solar Absorbance	Visible Light Reflectance		Winter U-Value	UV Rejected	Glare Reduction	Shading Coefficient	Total Solar Energy Rejected
					Interior	Exterior					
HP DS Series (Water activated Adhesive)											
50% (neutral)	47%	34%	23%	43%	12%	16%	1.06	99%	48%	0.55	50%
35% (neutral)	35%	26%	31%	43%	18%	27%	1.03	99%	58%	0.42	60%
25% (neutral)	27%	19%	36%	45%	20%	35%	1.03	99%	70%	0.36	67%
15% (neutral)	14%	10%	50%	40%	24%	54%	1.03	99%	85%	0.26	79%
50% Titanium-INF (neutral)	49%	49%	12%	39%	11%	12%	1.06	99%	47%	0.68	44%
35% Titanium- INF (neutral)	35%	35%	18%	47%	16%	17%	1.06	99%	61%	0.57	53%
20% Titanium INF (neutral)	23%	21%	26%	53%	27%	28%	1.04	99%	80%	0.43	65%
35% Silver	28%	22%	43%	35%	40%	44%	0.95	99%	69%	0.33	68%
20% Silver	15%	12%	55%	33%	58%	60%	0.94	99%	84%	0.25	79%
Specialty Series											
White Matte	64%	58%	17%	25%	21%		1.03	99%	28%	0.76	34%

Note: All data values above are representative and are provided for comparison purposes only.

MIDAS EXPORT USA CORPORATION
 7205 N.W. 68 STREET, SUITE # 7 - MIAMI, FL. 33166
 TEL: 305-888-8899 - FAX: 305-884-2070 - TOLL FREE: 1-888-MIDAS-22